

# PRODUCT SPECIFICATIONS – 8X

|                                     |  |
|-------------------------------------|--|
| <b>Videoconferencing Options</b>    | SX20 Codec with Cisco Precision 40 Camera 8x PTZ   |
| <b>Display</b>                      | <ul style="list-style-type: none"> <li>• 27" IPS LED</li> <li>• 2560 x 1440 Native Resolution</li> <li>• 178° Viewing Angle</li> <li>• 5 ms Response Time</li> </ul>   |
| <b>Control</b>                      | <ul style="list-style-type: none"> <li>• Integrated Panel with Touch Control for:             <ul style="list-style-type: none"> <li>- AutoDial/Connect</li> <li>- Disconnect</li> <li>- Camera Pan/Tilt/Zoom</li> <li>- Display Layout</li> <li>- Camera Mute (with LED Indicator)</li> <li>- Microphone Mute (with LED Indicator)</li> <li>- PC Source Selection (with LED Indicator)</li> <li>- Video Device Source Selection (with LED Indicator)</li> <li>- Volume</li> <li>- Stethoscope Mode (with LED Indicator)</li> <li>- Headphone Mode (with LED Indicator)</li> </ul> </li> <li>• RS232 Port for Expansion</li> </ul> |
| <b>Video Inputs</b>                 | <ul style="list-style-type: none"> <li>• Main Camera (Integrated)</li> <li>• 1 x DVI-D</li> <li>• 1 x VGA (HD15)</li> </ul>  |
| <b>Video Output</b>                 | 1 x HDMI (Dedicated to Display)  |
| <b>Audio Input</b>                  | <ul style="list-style-type: none"> <li>• 1 x Microphone (Integrated)</li> <li>• 1 x 3.5 mm Input (Side) / 1 x 3.5 mm Input (Front)</li> </ul>  |
| <b>Audio Output</b>                 | <ul style="list-style-type: none"> <li>• Integrated Speakers</li> <li>• 1 x 3.5mm Headphone Output</li> </ul>  |
| <b>Network</b>                      | 1 x 10/100/1G Ethernet   |
| <b>Dimensions (includes camera)</b> | <ul style="list-style-type: none"> <li>• 24" Wide</li> <li>• 17" High (Removable Speaker Deflector adds 1.25")</li> <li>• 5.5" Deep</li> </ul>   |
| <b>Weight</b>                       | 29.2 lbs   |
| <b>Mounting</b>                     | Compatible with 100mm x 100mm VESA Mounts  |
| <b>Electrical</b>                   | <ul style="list-style-type: none"> <li>• Integrated Auto Sensing Power Supply (100/240 volt 50/60 Hz)</li> <li>• 1 x IEC Type Inlet</li> </ul>   |

All specifications are subject to change

Iron Bow Healthcare Solutions, MEDiC™ and CLINiC™ logos are trademarks or registered trademarks of Iron Bow Technologies. (c) Iron Bow Healthcare Solutions. All rights reserved.

Patent Pending.